

Parkway Colors Collection

Style	Bond, Structure – 12 mil
Construction	Luxury Vinyl Plank Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.080" (2.0 mm)
Wear Layer Thickness	12 mil (0.30 mm)
Wear Layer	Enhanced Urethane
Edge Treatment	Square Edge
Sizes	12" x 24" (305 x 305 mm) 12" x 24" (305 x 610 mm)
Colors	16
Packaging	12" x 12" – 56 pcs, 56 sq.ft. (5.20 m2), 30 lbs (13.60 kg) 12" x 24" – 22 pcs, 44 sq.ft. (4.09 m2), 29 lbs (13.15 kg)
Adhesive	Porous & Non-porous Substrates: V-95 Full Spread 2-part Epoxy V-88 Full Spread, Transitional Pressure Sensitive, High Moisture XpressStep for LVT & Sheet Vinyl Full Coverage Spray XpressStep Premium for LFT Full Coverage High Moisture Spray Porous Substrates Only: V-82 Full Spread Note: Must use V-95, XpressStep or XpressStep Premium adhesive under hospital bends and heavy rolling load areas. Use V-95 where higher risk of topical moisture would be a concern
Installation Method	All arrows in the same direction. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.

Testing

HUD/FHA	Passes
ADAG (America Disability Act Guidelines)	Passes
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/in ft
Squareness (ASTM F540)	Passes - Max 0.010"
Static Load (ASTM F970 mod.)	Passes - 1,000 PSI: Residual Indent ≤ 0.005"
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm2
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather: 0.6 Rubber
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes

Environmental Data

Indoor Air Quality	FloorScore Certified; CDPH v1.1-2017
Product Declarations	EPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: IEQ4.1 Low Emitting Adhesives, IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization – EPDs; IEQc2 - Low Emitting
Manufacturing	Salem, NJ USA, ISO 14001 EMS Registered

For more information, contact your Mannington on Main representative or visit

ManningtonOnMain.com