

**Terrene Collection**

Style	Terrene
Classification	ASTM F1303 - Type II, Grade 1, Class A
Construction	Heterogeneous Sheet Non-ortho Phthalate
Total Thickness	.080" (2.03 mm)
Wear Layer Thickness	.055" (1.39 mm)
Finish	ScratchResist Pro
Width	6' 6" (2 meters)
Colors	10
Pattern Repeat	Random repeat, reverse sheet for seaming
Packaging	6' 6": 25 - 73 sq. yd. (25.1 - 61 sq. m)
Weight	5.4 lbs/yd <sup>2</sup> (2.93 kg/m <sup>2</sup> )
Adhesive	Porous and Non-Porous Substrates: V-81 Full Spread, Premium Latex
Seam Method	Mannington Commercial Weld Rods or MCS-42 Chemical Seam Sealer with VST-96 Application kit. Mannington Seam Coater Pen for high traffic areas. Note: Heat welding is the recommended procedure for healthcare and high traffic applications.

**Testing**

HUD/FHA	Passes
ADAG (American Disability Act Guidelines)	Passes
Flexibility (ASTM F137)	Passes – 1 ½" Mandrel - No Crack/Break
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes – 1,000 PSI, Residual Indent ≤ 0.005"
Residual Indentation (ASTM F1914)	Passes – ≤0.007"
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather: 0.6 Rubber
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes

**Environmental Data**

Indoor Air Quality	FloorScore Certified; CDPH v1.1-2017
Product Declarations	EPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: IEQ4.1 Low Emitting Adhesives, IEQ.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization – EPDs; IEQc2 - Low Emitting Materials
Manufacturing	Salem, NJ USA, ISO 14001 EMS Registered

For more information, contact your Mannington on Main representative or visit

**ManningtonOnMain.com**