

PRODUCT SPECIFICATIONS

Parkway Rigid Collection

Style	Plank- 7.1"x 48"	Rectangle- 12"x 24"	
Construction	SPC Plank	SPC Tile	
	Non-ortho Phthalate	Non-ortho Phthalate	
Classification	ASTM F3261 Class I, Type B	ASTM F3261 Class I, Type B	
	Grade 2, Backing Class B	Grade 2, Backing Class B	
Total Thickness	0.157" (4.0 mm) SPC	0.157" (4.0 mm) SPC	
	.039" (1.0 mm) IXPE Pad	.039" (1.0 mm) IXPE Pad	
Wear Layer Thickness	20 mil (0.50 mm)	20 mil (0.50 mm)	
Wear Layer	Enhanced Urethane	Enhanced Urethane	
Edge Treatment	Painted Bevel	Painted Bevel	
Sizes	7.1" x 48" (180.34 x 1219 mm)	12" x 24" (305 x 610 mm)	
Colors	9 each style	3 each style	
Packaging	7.1" x 48" 10pcs	12" x 24" 12 pcs	
	23.77 ft2 (2.21 m2)	24.03 ft2 (2.23 m2)	
	40.9 lbs (19 kg)	41.1 lbs (19 kg)	
Installation Method	All arrows in the same direction. Tiles should be installed block or staggered		
·	when quarter turned, arrows should alternate.		
	,,		

Testing

HUD/FHA	Passes	
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/lin ft	
Squareness (ASTM F540)	Passes - Max 0.010"	
Static Load (ASTM F970)	Passes - 750 PSI; Residual Indent ≤ 0.005"	
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm2	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather: 0.6 Rubber	
Acoustic IIC (ASTM E492)	67 - 6" Concrete with Drop Ceiling	
Acoustic STC (ASTM E90)	61 - 6" Concrete with Drop Ceiling	
Resistance to Light (ASTM F1515)	Passes	
Chemical Resistance (ASTM F925)	Passes	
Resistance to Heat (ASTM F1514)	Passes	

Environmental Data

Indoor Air Quality Product Declarations LEED Scoreboard	FloorScore Certified; CDPH v1.1-2017 EPD May contribute to LEED credits: LEED 2009: IEQ4.1 Low Emitting Adhesives - no adhesive needed; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization – EPDs; IEQc2 -
Manufacturing	Low Emitting Materials Vietnam