

Reset® Recycled Rubber Sports Flooring

Style	Reset®
Construction	Recycled Rubber Sports Flooring
Classification	ASTM F3041 Class A, Type II (Tile); Class B, Type I (Sheet)
Total Thickness	3/8" (9.0 mm) (Nominal)
Sizes	18" x 18" (457 x 457 mm) Square Edge 24" x 24" (610 x 610 mm) Interlocking 4' x 50' (1.2 x 15 m) Sheet
Colors	9
Packaging	18" x 18" - 1 pc, 2.25 ft ² (0.209 m ²), 4.365 lbs (1.98 kg) 24" x 24" - 1 pc, 4 ft ² (0.3716 m ²), 8 lbs (3.629 kg) 4' x 50' Sheet - 200 ft ² (18.58 m ²) Roll, 412 lbs (186.9 kg)
Adhesive	MR-710 Full Spread, Urethane MR-725 Full Spread, 2-part Urethane Note: Adhesives are for 18" x 18" tile and sheet only. No adhesive needed for 24" x 24" interlocking tile.

Testing

HUD/FHA	Meets or Exceeds
ADAG (American Disability Act Guidelines)	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.40%
Squareness (ASTM F540)	Passes - Max 0.030"
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 400 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change
Abrasion Resistance (ASTM D3389)	Passes - < 1g, 1000 Cycles

Environmental Data

Recycled Content	Black Tones contains a minimum of 91% post-consumer recycled content (Class A) by total product weight. All other colors in Reset contain a minimum of 4% pre-consumer and a minimum of 72% post-consumer recycled Content (Class B) by total product weight.
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosure & Optimization - Material Ingredients: IEQc2 - Low Emitting Materials.
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information
Manufacturing	Made in the USA

Warranty

Limited 5 Year Commercial Warranty

For more information, contact your Mannington on Main representative or visit