

ColorScape® & ColorSpec® Rubber Tile Flooring (Thermoset Rubber)

Style	ColorScape® Tile	ColorSpec® Tile
Construction	Thermoset Rubber Tile	Thermoset Rubber Tile
Classification	ASTM F1344 Class 1, Type A	ASTM F1344 Class 1, Type A
Total Thickness	1/8" (3.175 mm)	1/8" (3.175 mm)
Profile	Square, Sculptured, Round	Square, Sculptured, Smooth
Sizes	Square - 18.125" x 18.125" (460 x 460 mm) 36.25" x 36.25" (920.75 x 920.75 mm) Sculptured - 18.125" x 18.125" (460 x 460 mm) 36" x 36" (914.4 x 914.4 mm) Round - 18.125" x 18.125" (460 x 460 mm) 36.125" x 36.125" (917.7 x 917.7 mm)	Square - 18.125" x 18.125" (460 x 460 mm) 36.25" x 36.25" (920.75 x 920.75 mm) Square - 18.125" x 18.125" (460 x 460 mm) 36" x 36" (914.4 x 914.4 mm) Smooth - 18" x 18" (457.2 x 457.2 mm) 36" x 36" (914.4 x 914.4 mm)
Finish	Matte	Matte
Colors	36	36
Packaging	18.125" x 18.125" - 20 pcs, 45.625 ft ² (4.239 m ²) 43 lbs. (19.5 kg.) All other sizes sold per piece	18" x 18" - 20 pcs, 45 ft ² (4.181 m ²), 42.6 lbs. (19.32 kg.) 18.125" x 18.125" - 20 pcs, 45.625 ft ² (4.239 m ²) 43 lbs. (19.5 kg.) All other sizes sold per piece
Adhesive	MR-725 Full Spread, 2-part Urethane MR-919 Full Spread, General Purpose Acrylic Note: Must use MR-725 adhesive under hospital beds and heavy rolling loads or where high performance is needed.	MR-725 Full Spread, 2-part Urethane MR-919 Full Spread, General Purpose Acrylic Note: Must use MR-725 adhesive under hospital beds and heavy rolling loads or where high performance is needed.

Testing

HUD/FHA	Meets or Exceeds
ADAG (American Disability Act Guidelines)	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.15%
Squareness (ASTM F540)	Passes - Max 0.010"
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 500 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change

Environmental Data

Rapidly Renewable Content	Contains 4% rapidly renewable resource content
Indoor Air Quality	FloorScore Certified
Product Declarations	EPD
LEED Scoreboard	May contribute to LEED credits LEED 2009: MRc5 Regional Materials; MRc6 Rapidly Renewable Materials; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials IEQc2 - Low Emitting Materials
mindfulMaterials Manufacturing	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information Calhoun, GA (USA)

Warranty

Limited 10 Year Commercial Warranty
Limited 10 Year Wear Warranty

- ColorScape and ColorSpec formulations are made with superior rubber so they retain their amazing color, resist indentations and cracking, and are quiet underfoot. Built-in waxes produce a natural luster that requires no finish or stripping, lowering maintenance costs.
- ColorScape and ColorSpec are not recommended in commercial areas that require static dissipation.
- In spaces that will receive rubber flooring and accessories, maintain a minimum temperature of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed.
- Dirt, wetness and improper maintenance may cause significant variation in product appearance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substance from being tracked onto floor.

For more information, contact your Mannington on Main representative or visit