

Towne Centre Collection

| Style | Barrel Oak, Ridgewood | Dunham | Textile |
|-------------------------|--|---|--|
| Construction | Heterogeneous Sheet Non-ortho Phthalate | Heterogeneous Sheet Non-ortho Phthalate | Heterogeneous Sheet Non-ortho Phthalate |
| Classification | ASTM F1303 Type I Grade 1, Class B | ASTM F1303 Type I Grade 1, Class B | ASTM F1303 Type I Grade 1, Class B |
| Total Thickness | 0.080" (2.03mm) | 0.080" (2.03 mm) | 0.080" (2.03mm) |
| Wear Layer Thickness | 0.020" (0.51 mm) | 0.020" (0.51 mm) | 0.020" (0.51 mm) |
| Wear Layer | ScratchResist® Pro w/Microban® Antimicrobial Protection | ScratchResist® Pro w/Microban® Antimicrobial Protection | ScratchResist®Pro w Microban® Antimicrobial Protection |
| Width | 6' (1.83 m), 12' (3.66m) | 6' (1.83 m), 12' (3.66 m) | 6' (1.83 m), 12' (3.66 m) |
| Colors | 4 each style | 4 each style | 4 each style |
| Pattern Repeat | 48" Lx 48" W (1.22 x 1.22 m) | 36" Lx 36" W (0.91 x 0.91 m) | 36" L x 72" W (0.91 x 1.83 m) |
| Packaging | 6' -30-50 sq yd 12' - 30-100 sq yd (25.0-41.8 mm) | 6' -30-50 sq yd 12' - 30-100 sq yd (25.0-41.8 mm) | 6' -30-50 sq yd 12' - 30-100 sq yd (25.0-41.8 mm) |
| Weight | 4.90 lbs/sq yd (2.66 kg/mm) | 4.90 lbs/sq yd (2.66 kg/mm) | 4.90 lbs/sq yd (2.66 kg/mm) |
| Adhesive | Porous & Non-porous Substrates V-88 Full Spread, Transitional Pressure Sensitive, High Moisture V-95 Full Spread, 2-part Epoxy XpressStep for LVT & Sheet Vinyl Full Coverage Spray | | |
| Porous Substrates Only: | V-82 Full Spread Note: Must use V-95 or XpressStep adhesive under heavy rolling load areas. Use V-95 where higher risk of topical moisture would be a concern. | | |
| Seam Method | Mannington Commercial Weld Rods or MLG-33 Chemical Seam Sealer. Mannington Seam Coater Pen for high traffic areas. Note: Heat welding is the recommended procedure for heavy commercial and high traffic applications. | | |

Testing

| | |
|---|--|
| HUD/FHA | Passes |
| ADAG (American Disability Act Guidelines) | Passes |
| Flexibility (ASTM F137) | Passes – 1/4" Mandrel - No Crack/Break |
| Static Load (ASTM F970 mod.) | Passes - 1,500 PSI: Residual Indent ≤ 0.005" |
| Residual Indentation (ASTM F1914) | Passes - < 0.012" |
| Slip Resistance (ASTM C1028) | Passes - ≥ 0.5 Leather: 0.6 Rubber |
| Resistance to Light (ASTM F1515) | Passes |
| Chemical Resistance (ASTM F925) | Passes |
| Resistance to Heat (ASTM F1514) | Passes |

Environmental Data

| | |
|----------------------|---|
| Indoor Air Quality | FloorScore Certified; CDPH v1.1-2017 |
| Product Declarations | EPD |
| LEED Scoreboard | May contribute to LEED credits: LEED 2009: IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials – Flooring LEED v4: Building Product Disclosure & Optimization – EPDs; IEQc2 - Low Emitting Materials |
| Manufacturing | Salem, NJ USA, ISO 14001 EMS Registered |

For more information, contact your Mannington on Main representative or visit