## **Parkway Colors Collection**

Style	Bond, Structure – 12 mil
Construction	Luxury Vinyl Plank Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.080" (2.0 mm)
Wear Layer Thickness	12 mil (0.30 mm)
Wear Laver	Enhanced Urethane
Edge Treatment	Square Edge
Sizes	12 <sup>°</sup> x 12° (305 x 305 mm)
	12" x 24" (305 x 610 mm)
Colors	16
Packaging	12" x 12" – 56 pcs, 56 ft² (5.20 m²), 30 lbs (13.60 kg)
	12" x 24" – 22 pcs, 44 ft² (4.09 m²), 29 lbs (13.15 kg)
Adhesive	Porous & Non-porous Substrates:
	V-95 Full Spread 2-part Epoxy
	V-88 Full Spread, Transitional Pressure Sensitive, High Moisture
	XpressStep for LVT & Sheet Vinyl Full Coverage Spray
	Note: Must use V-95, XpressStep adhesive under hospital beds and heavy rolling load
	areas. Use V-95 where higher risk of topical moisture would be a concern.
	Full Glue, please visit www.manningtononmain.com for full installation instructions.
Installation Method	

## Testing

HUD/FHA ADAG (America Disability Act Guidelines) Flexibility (ASTM F137) Dimensional Stability (ASTM F2199) Squareness (ASTM F540) Static Load (ASTM F970 mod.) Residual Indentation (ASTM F1914) Flooring Radiant Panel (ASTM E648) Smoke Density (ASTM E662) Slip Resistance (ASTM C1028) Resistance to Light (ASTM F1515) Chemical Resistance (ASTM F925) Resistance to Heat (ASTM F1514)

## **Environmental Data**

Indoor Air Quality Product Declarations LEED Scoreboard

Manufacturing

Passes Passes Passes - 1" Mandrel - No Crack/Break Passes - Max 0.020 in/lin ft Passes - Max 0.010" Passes - 1,000 PSI: Residual Indent  $\leq 0.005$ " Passes - 2 8% Avg / 10% Single Value Passes - Class 1;  $\geq 0.45$  watts/cm<sup>2</sup> Passes -  $\leq 450$ Passes -  $\geq 0.5$  Leather: 0.6 Rubber Passes Passes Passes Passes

FloorScore Certified; CDPH v1.2-2017 EPD May contribute to LEED credits: LEED 2009: IEQ4.1 Low Emitting Adhesives, IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization – EPDs; IEQc2 - Low Emitting Salem, NJ USA, ISO 14001 EMS Registered

For more information, contact your Mannington on Main representative or visit