

Parkway Rigid Collection

Style	Plank- 7.1"x 48"	Rectangle- 12"x 24"
Construction	SPC Plank	SPC Tile
Classification	Non-ortho Phthalate ASTM F3261 Class I, Type B Grade 2, Backing Class B	Non-ortho Phthalate ASTM F3261 Class I, Type B Grade 2, Backing Class B
Total Thickness	0.157" (4.0 mm) SPC .039" (1.0 mm) IXPE Pad	0.157" (4.0 mm) SPC .039" (1.0 mm) IXPE Pad
Wear Layer Thickness	20 mil (0.51 mm)	20 mil (0.51 mm)
Wear Layer	Enhanced Urethane	Enhanced Urethane
Edge Treatment	Painted Bevel	Painted Bevel
Sizes	7.1" x 48" (180.34 x 1219 mm)	12" x 24" (305 x 610 mm)
Colors	9 each style	3 each style
Packaging	7.1" x 48" 10pcs 23.77 ft ² (2.21 m ²) 40.9 lbs (19 kg)	12" x 24" 12 pcs 24.03 ft ² (2.23 m ²) 41.1 lbs (19 kg)
Installation Method	Floating	

Testing

HUD/FHA	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/in ft
Squareness (ASTM F540)	Passes - Max 0.010"
Static Load (ASTM F970)	Passes - 750 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel (ASTM E648) Smoke Density (ASTM E662)	Passes - Class 1; ≥ 0.45 watts/cm ²
Slip Resistance (ASTM C1028)	Passes - ≤ 450
Acoustic IIC (ASTM E492)	Passes - ≥ 0.5 Leather: 0.6 Rubber
Acoustic STC (ASTM E90)	67 - 6" Concrete with Drop Ceiling
Resistance to Light (ASTM F1515)	61 - 6" Concrete with Drop Ceiling Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes

Environmental Data

Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017
Product Declarations	EPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: IEQ4.1 Low Emitting Adhesives - no adhesive needed; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization – EPDs; IEQc2 - Low Emitting Materials
Manufacturing	Vietnam

For more information, contact your Mannington on Main representative or visit

ManningtonOnMain.com